

RETRACT-A-LINE

WL/002 POWDER COATED

INSTALLATION / OPERATING INSTRUCTIONS

LOCATION

- Find a suitable position to install your RETRACT-A-LINE
- You require a minimum area of 0.6m x 8m for RETRACT-A-LINE model WL/002 - 5 lines by 8 meters. Do not exceed 8 meters.
- In addition to the above, it is recommended that you leave 0.6m on at least one side over the full length to allow free access to the laundry.
- The ideal height is between 1.6 – 1.8 meters.
- Refer to the Minimum / Recommended Area Requirements schematic drawings.

INSTALLATION

CABINET

- Place the cabinet on the wall with the tensioning knob on the right hand side.
- Ensure that the cabinet is level and accurately mark the holes onto the wall.
- Refer to the Mounting Holes schematic drawings.
- Ensure that the holes will be drilled into solid brick and not mortar or a hollow brick.
- Drill the holes with an 8mm masonry drill.
- Hammer the plugs into the holes.
- Fix the cabinet to the wall with the couch bolts and washers (Make use of the washers to maximize the holding power)

HOOK

- The hook must be placed directly opposite the cabinet;
 - It must be in the center of the cabinet both in height and in width.
- Ensure that the hook part faces upwards.
- Ensure that the hook is level and accurately transfer the holes onto the wall.
- Ensure that the holes will be drilled into solid brick and not mortar or a hollow brick.
- Drill the holes with an 8mm masonry drill.
- Hammer the plugs into the holes.
- Fix the hook to the wall with the couch bolts and washers (Make use of the washers to maximize the holding power)

WARNING!

- **THE UNIT IS FACTORY ASSEMBLED AND UNDER HIGH TENSION**
- **DO NOT** allow the pull-bar to return un-controlled – it **WILL** result in personal injury and damage to the unit.
- Wear eye protection during installation.

- **DO NOT** allow children to play / swing / hang on the lines, as this **WILL** result in personal injury and damage to the unit.
- **DO NOT** tamper with the unit as this **WILL** result in personal injury and damage to the unit.
- During strong winds, remove your washing to prevent damage to the unit.
- **NB! STRANGULATION DANGERS**

OPERATION

EXTENDING

- Disengage the gear wheel by pushing the locking lever (red lever) flat against the cabinet.
- Take the pull-bar, in a straight line, to the hook and engage the handle firmly into the hook.
- Engage the gear wheel by pushing the lock lever (red lever) to the center position.
- Turn the tensioning knob anti-clock wise until the lines are tight – note that all lines will not tension equally.
- Unhook the slack lines from the cleat at the pull bar end and pull tight – re-engage line into the cleat again.

RETRACTING

- Remove all laundry from the line – including pegs.
- Disengage the gear wheel by pushing the locking lever (red lever) flat against the cabinet.
- Unhook the pull-bar and return it in a controlled manner, straight back to the cabinet.

CARE

- Always wipe your lines clean before use.
- Always return the pull-bar to the cabinet after use.
- Do not overload. Load rated at 40Kg evenly distributed.

RE-STRINGING

NB! THIS IS AN EXTREMELY DANGEROUS OPERATION AND MUST BE DONE BY TWO COMPETANT PERSSONS.

NB! READ THESE INSTRUCTIONS CAREFULLY AND UNDERSTAN WHAT YOU MUST DO BEFORE ATTEMPTING TO DO SO.

- **NB! Extreme care must be taken as this could result in personal injury to you or bystanders and could damage the unit.**
- **NB! When performing this operation prevent children / pets from accidently distracting you which could lead to personal injuries.**
- Remove the pull-bar from the cabinet and pull it away until completely unwound.

- Make sure that the tying eyes on the drum are visible through the opening and facing the front.
- Secure the pull-bar positively to a fixed stationary object.
- Engage the locking lever (red lever) to prevent re-winding.
- **NB! Replace one line at a time only.**
- Untie the line from the pull-bar and cut the knot at the drum end.
- NB! Use only original STARLINE SILK STEEL REPLACEMENT LINE , reference code NPS/SSCL-52 for the 5 line unit.
- Cut the replacement line into 5 lengths of 8.2 meters.
- Feed the end of the line through the eye, from the top, and make a “figure eight knot” on the line and pull tight.
- Feed the other end through the cleat on the pull-bar and lock into position.
- Repeat this with all the other lines.
- Carefully disengage the locking lever (red lever).
- Release the pull-bar from the secure position.
- Return the pull-bar in a controlled manner.
- Draw the pull-bar up to its normal operating position and back a few times to ensure that it is operating smoothly.

GUARANTEE

Please refer to the Product Guarantee Policy on the Website at www.star-line.co.za

Copy right rest in NA Manufacturing (Pty) Ltd.